



Tron 40S MkII



www.jotron.com



▶ Tron 40S MkII

Float free and manual GMDSS EPIRB with new state of the art technology. Improved visibility when activated. Fits existing bracket.



SPECIFICATIONS	
TECHNICAL	
Battery:	Lithium metal, 7,2V/7200 mAh, 5 years service life
Dimensions:	Height 379mm Diameter 180mm
Weight:	2kg
Material:	Glass-reinforced polycarbonate
Compass safe distance:	1.5m
Temperature range:	-20°C to + 55°C (operating) -30°C to +65°C (storage)
Operating life:	Minimum 48 hours at -20°C
Antenna:	Omni directional
Cospas-Sarsat Transmitter	
Frequency:	406.037 MHz
Output power: Homing transmitter	5W
Frequency:	121.500 MHz
Output power:	Up to 100 mW
Protocols:	Maritime, serialized, radio call sign
ACCESSORIES	
Bracket:	Float-free: FB-6
Battery:	Replacement kit
Hydrostatic release:	HRU kit
WARRANTY	5 years

Agent/Distributor:

Jotron AS reserves the right to change the design and/or specifications at any time without prior notice. Reservations are also taken towards any general errors that may occur.

v.F

www.jotron.com

CONTACT INFORMATION

Jotron AS
P.O.Box 54
3281 Tjodalyn
Norway
Tel: +47 33 13 97 00
Fax: +47 33 12 67 80
sales@jotron.com

Jotron UK Ltd.
Crosland Park
Cramlington
NE23 1LA
United Kingdom
Tel: +44 (0) 1670 712000
Fax: +44 (0) 1670 590265
sales@jotron.com

Jotron Asia Pte. Ltd.
19 Loyang Way
Changi Logistics Centre
Rear Office Block 04-26
Singapore 508724
Tel: +65 65426350
Fax: +65 65429415
sales@jotron.com

Jotron USA, Inc.
10645 Richmond Avenue, Suite 170
Houston, TX 77042
USA
Tel: +1 713 268 1061
Fax: +1 713 268 1062
sales@jotron.com