

NVX-1000 NAVTEX



• FEATURES

- 5.7" Silver Bright LCD.
- Supports all IMO NAVTEX frequencies (518kHz, 490kHz and 4209.5kHz).
- Displays the message contents.
- Messages stored for 72 hours.
- Simple to operate.
- Desktop or flush mount.
- External printer interface and External alarm output.
- Low power consumption.
- CCS type approval.

• SPECIFICATIONS

NAVTEX Receiver	
Receiving Frequency:	518kHz, 490(or 486)kHz and 4209.5kHz
Mode of Reception:	F1B
Sensitivity:	2 μ V e.m.f. (50 Ω), 4% error rate or less
Display	
Display System:	5.7", 103(W)mm \times 79(H)mm, 320 \times 240 dots
Display Modes:	Message List, Main Menu
Messages Storage:	200 messages \times 3 channels
Power Supply	24V DC (10~38V)
Environment Conditions	
Receiver:	-15 $^{\circ}$ C ~ +55 $^{\circ}$ C
Antenna:	-25 $^{\circ}$ C ~ +70 $^{\circ}$ C
Printer Interface	RS-232
Dimension & Weight	
Weight:	1.0 kg (main unit)
Dimension:	264(W) \times 145(H) \times 80(D) mm (main unit)